Modular Cooking Range Line 700XP Full Module Electric Fry Top, Mild Steel



Modular Cooking Range Line

700XP Full Module Electric Fry Top, Mild Steel

371186 Full module electric fry top with smooth mild steel plate, thermostatic control

371199 Full module electric fry top with smooth mild steel plate, thermostatic control

371187 Full module electric fry top with 2/3 smooth and 1/3 ribbed mild steel plate, thermostatic control

371200 Full module electric fry top with 2/3 smooth and (E7FTEHSPIN) Full module electric fry top with 2/3 smooth and 1/3 ribbed mild steel plate, thermostatic control

Short Form Specification

Item No.

To be installed on open base installations or bridging supports. Smooth cooking surface in mild steel. Temperature range from 110°C to 280°C. Removable drawer below the cooking surface for the collection of grease and fat. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- Unit to be mounted on open base cupboards, bridging supports or cantilever systems.
- Large drain hole on cooking surface permits the draining of fat into large 1,5 liter collector placed under the cooking surface.
- Large grease collection container available as optional accessory to be installed under top units over open base cupboard.
- Safety thermostat and thermostatic control.
- Stainless steel high splash guard on the rear and sides of cooking surface. Splash guard can be easily removed for cleaning.
- Scrapers with smooth or ribbed blades included as standard.
- Temperature range of griddle from 110 °C to 300 °C.
- IPX 4 water protection.
- Infrared heating elements mounted below the cooking surface.

Construction

- Cooking surface in mild steel for optimum grilling results.
- Cooking surface to be completely smooth or 2/3 smooth and 1/3 ribbed.
- Exterior panel in Stainless Steel with Scotch Brite finish
- One piece pressed 1.5 mm work top in Stainless steel.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

Optional Accessories

Scraper for smooth plate fry tops

•	Scraper for ribbed plate fry tops (only for 371187, 371200)	PNC 164257 ☐
•	4 wheels, 2 swivelling with brake (700/900XP). It is mandatory to install with base supports for feet/wheels. (only for 371186, 371187)	PNC 206135 □
•	Support for bridge type system, 800mm	PNC 206137 □
•	Support for bridge type system, 1000mm	PNC 206138 ☐
•	Support for bridge type system, 1200mm	PNC 206139 □
•	Support for bridge type system, 1400mm	PNC 206140 □
•	Support for bridge type system, 1600mm	PNC 206141

APPROVAL:

PNC 164255




Modular Cooking Range Line 700XP Full Module Electric Fry Top, Mild Steel


Water coulumn with swivel arm (water column extension not included)	PNC 206289 □
 Water column extension for 700 line 	PNC 206291 🖵
 Chimney upstand, 800mm 	PNC 206304 🗆
 Right and left side handrails 	PNC 206307 🖵
 Grease/oil kit container for 700 line frytops (half and module) and 900 line frytops (module) 	PNC 206346 □
 Rear paneling - 800mm (700/900) (only for 371186) 	PNC 206374 🗖
• Rear paneling - 1000mm (700/900) (only for 371186)	PNC 206375 □
Chimney grid net, 400mm	PNC 206400 🖵
• - NOT TRANSLATED - (only for 371187, 371200)	PNC 206420 □
Frontal handrail 800mm	PNC 216047 🖵
Frontal handrail 1200mm	PNC 216049 🖵
 Frontal handrail 1600mm 	PNC 216050 🖵
• Large handrail - portioning shelf, 400mm	PNC 216185 🖵
• Large handrail - portioning shelf, 800mm	PNC 216186 🖵
• 2 side covering panels for top appliances	PNC 216277 🖵






Modular Cooking Range Line 700XP Full Module Electric Fry Top, Mild Steel





EI = Electrical connection



Electric

Supply voltage:				
371186 (E7FTEHSSIO)	400 V/3N ph/50/60 Hz			
371199 (E7FTEHSSIN)	230 V/3 ph/50/60 Hz			
371187 (E7FTEHSPIO)	400 V/3N ph/50/60 Hz			
371200 (E7FTEHSPIN)	230 V/3 ph/50/60 Hz			
Connected load:				
371186 (E7FTEHSSIO)	8.4 kW			
371199 (E7FTEHSSIN)	7.8 kW			
371187 (E7FTEHSPIO)	8.4 kW			
371200 (E7FTEHSPIN)	7.8 kW			
Total Watts:				
371186 (E7FTEHSSIO)	8.4 kW			
371199 (E7FTEHSSIN)	7.8 kW			
371187 (E7FTEHSPIO)	8.4 kW			
371200 (E7FTEHSPIN)	7.8 kW			

Key Information

Cooking surface width:	730 mm
Cooking surface depth:	540 mm
Working Temperature MIN:	110 °C
Working Temperature MAX:	300 °C
Net weight:	70 kg
Shipping weight:	
371186 (E7FTEHSSIO)	75 kg
371199 (E7FTEHSSIN)	84 kg
371187 (E7FTEHSPIO)	84 kg
371200 (E7FTEHSPIN)	84 kg
Shipping height:	540 mm
Shipping width:	820 mm
Shipping depth:	
371186 (E7FTEHSSIO)	850 mm
371199 (E7FTEHSSIN)	860 mm
371187 (E7FTEHSPI0)	860 mm
371200 (E7FTEHSPIN)	860 mm
Shipping volume:	0.38 m ³

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

