

## Digital Undercounter ecostore HP Refrigerated Counter - 3 Door (R134a) with top and upstand


ITEM # \_\_\_\_\_

MODEL # \_\_\_\_\_

NAME # \_\_\_\_\_

SIS # \_\_\_\_\_

AIA # \_\_\_\_\_


**710434 (EJ3R3AAA)**

 3-door Refrigerated  
 Counter, -2+10°C (R134A),  
 with upstand

### Short Form Specification

#### Item No.

Internal and external doors, front and side panels in 304 AISI stainless steel. N.3 doors. With top and upstand. Built-in refrigeration unit. Ventilated. Refrigerant R134a. High-density expanded polyurethane foam, 90 mm in thickness, with cyclopentane injection. Digital control panel. Completely automatic defrosting and automatic evaporation of defrost water obtained by hot gas. Temperature range: -2+10°C. CFC and HCFC free. Feet in 304 AISI stainless steel, adjustable in height.

**APPROVAL:** \_\_\_\_\_

### Main Features

- Tropicalized unit (43°C ambient temperature).
- Kit 1/3 drawers available as accessory.
- Digital control panel allowing the easy and precise setting and control of the internal temperature.
- Operating temperature can be adjusted from -2 to +10 °C to suit different food storage requirements.
- This appliance is intended for use in ambient temperatures up to 40°C.
- Complies with main international certification bodies and is CE marked.
- Kit 1/2 drawers available as accessory.
- The door self-closes when opened less than at a 90° angle and is equipped with a door seal to guarantee perfect closure.
- Completely automatic defrosting and automatic evaporation of defrost water by hot gas.
- Forced air cooling system guaranteeing great uniformity of the temperature in the counter and excellent conservation of the food quality.
- High standards of hygiene and ease of cleaning are guaranteed by the rounded internal corners of the cabinet and easily removable runners and grids.

### Construction

- Built-in compressor to suit operating conditions.
- CFC and HCFC free.
- Legs in 304 AISI stainless steel (150 mm high, adjustable in height), with plastic interior.
- Internal and external doors, front and side panels and 50mm thick removable worktop in 304 AISI stainless steel.
- Back panel in galvanized steel.

### Included Accessories

- 3 of Kit 1/1 grey rilsan grid and 2 side runners for refrigerated counters PNC 881109

### Optional Accessories

- 1/1GN grey rilsan grid for refrigerated counters PNC 881107
- 2 side runners for 1/1 GN ecostore refrigerated counters PNC 881108
- Kit 1/1 grey rilsan grid and 2 side runners for refrigerated counters PNC 881109
- 1/1 GN plastic container, H=65 mm PNC 881110
- 1/1 GN plastic container, H=100 mm PNC 881111
- 1/1 GN plastic container, H=150 mm PNC 881112
- 2x½ drawer kit for refrigerated counters - h650mm PNC 881176
- 3x1/3 drawer kit for refrigerated counters - h650mm (only for refrigerated counters) PNC 881177
- Kit 4 wheels, H=100 mm (2 with brakes) for refrigerated counters PNC 881191



**Electrolux**  
PROFESSIONAL

## Digital Undercounter ecostore HP Refrigerated Counter - 3 Door (R134a) with top and upstand


- Kit 4 wheels, H=150 mm (2 with brakes) PNC 881193   
for 2&3 compartment refrigerated  
counters
- Lock for refrigerated counters with three PNC 881246   
compartments - h650mm



Digital Undercounter  
ecostore HP Refrigerated Counter - 3 Door (R134a) with top and  
upstand  
The company reserves the right to make modifications to the products  
without prior notice. All information correct at time of printing.

2020.05.05

## Digital Undercounter ecostore HP Refrigerated Counter - 3 Door (R134a) with top and upstand



### Electric

Supply voltage:	710434 (EJ3R3AAA)	220-240 V/1 ph/50 Hz
Electrical power max.:		0.22 kW

### Key Information:


Gross capacity:	
Net Volume:	245.4 lt
N° of doors:	
External dimensions, Width:	1699 mm
External dimensions, Height:	950 mm
External dimensions, Depth:	700 mm
Internal Dimensions (depth):	560 mm
Internal Dimensions (height):	510 mm
Internal Dimensions (width):	1252 mm
Net weight:	114 kg
Shipping volume:	1.49 m <sup>3</sup>
Depth with doors open:	1310 mm

### Refrigeration Data

Control type:	Digital
Compressor power:	1/4 hp
Refrigerant type:	R134a
GWP Index:	1300
Refrigeration power:	358 W
Refrigerant weight:	120 g
Min/Max internal humidity:	40/85
Operating temperature min.:	-2 °C
Operating temperature max.:	10 °C
Operating mode:	Ventilated

### Product Information (EU Regulation 2015/1094)

Energy Class:	B
Yearly and daily energy consumption:	605kWh/year - 1.66kWh/24h
Climate class:	Heavy Duty (5)
Energy Efficiency Index (EEI):	25.03



### EU energy labelling from 1st July 2016

The European energy labelling scheme for professional refrigerators and freezers is based on requirements setting Minimum Energy Performance standards for commercial refrigeration cabinets sold within the EU. These requirements are designed to drive energy efficiency and environmentally friendly approach for professionals. The European energy labelling scheme will apply to all manufacturers and importers who sell and market products within the EU and it is mandatory across Europe.

Important: all products which consume energy above the minimum level will not be able to be sold within the EU from 1 July 2016.